



SRP Thermocouple Data Logger

Eight-Channel Temperature Data Logger

SRP Thermocouple data logger is ideal for monitoring temperature over a wide range. Easily and accurately record temperature from any J, K, S, T or E type thermocouple probe. With seven inputs for thermocouple probes and an on-board cold-junction thermistor, the SRP-TC8 logger is one of the most versatile thermocouple data loggers available.

APPLICATIONS

Monitor performance of gas-fired heating equipment, verifying concrete curing temperatures, process verification, etc.

GENERAL SPECIFICATIONS

Size:	107mm x 74mm x 22mm (4.2" x 2.9" x 0.9")
Weight:	110 gm
Case Material:	Noryl® Plastic
Battery:	3.6 volt Lithium
Resolution:	12-bit (1 part in 4096)
Mounting:	Magnetic backing or locking eyelet
Clock Accuracy:	± 2 seconds per day
Sampling Methods:	Continuous (First-in First-out)*, Stop When Full (Fill-then-stop) <i>*Not available with sample rates faster than eight seconds</i>
Operating Limits:	-40°C to 70°C and 0 to 95% RH (non-condensing)
PC Requirements:	Windows PC with at least one free USB or serial port (depending on interface)
Software Requirements:	TrendReader® 2 (Compatible with Windows 2000 SP4, XP SP1 and Vista 32 bit)
Memory Size:	32 KB (capable of storing up to 21,500 readings) 128 KB (capable of storing up to 87,000 readings) 1.5 MB (capable of storing up to 1,048,000 readings)
(3 models available)	
Sampling Rates:	User selectable rates from 25 per second to once every eight hours (Note: battery pack or power supply required for sampling rates faster than eight seconds)
Number of Channels:	Eight (one internal thermistor for cold-junction compensation and seven thermocouple inputs)



SENSOR SPECIFICATIONS

Internal Temperature Sensor

Type:	NTC Thermistor - 10,000 Ohm @ 25°C
Range:	-40°C to 70°C
Accuracy:	±0.2°C over the range of 0°C to 70°C
Resolution:	0.03°C @ 25°C; better than 0.07°C between -25°C and 70°C; better than 0.13°C between -40°C and -25°C

Thermocouple Wire	Range	Resolution
J Type	-50°C to 600°C	0.30°C
K Type	-100°C to 1150°C	0.50°C
S Type	0°C to 1450°C	1°C
T Type	-200°C to 400°C	0.40°C
E Type	-50°C to 680°C	0.24°C

Accuracy: ±0.5% of range + resolution

ORDERING INFORMATION

Model No.:	Memory Size:
SRP-TC8-32K	32K
SRP-TC8-128K	128K
SRP-TC8-1.5M	1.5M